SLIDE

TECHNICAL DATA SHEET

40012N Paintable Mold Release Aerosol

Product Description



Seguro para ser usado con todos los plásticos Use where parts must be painted, hot stamped or metalized Para uso en partes que tienen que pintárse, estampárse a calor o metalizárce

> Net. Wt.11.5 oz. (327g) For industrial use only-ra uso industrial solame

Applications	Mold Release
Unit Package Description	16 ounce aeroso
Generic Description	Paintable Mold F
Net Weight Fill	11.5 net ounces
UPC Code	858799000004
Units Per Case	12
Case Weight (Ibs)	13
Appearance	Clear Oily Color
Flash Point F	Not Determined
Flash Point C	Not Determined
Base Type	Paintable Silicor
Evaporation Rate	Fast
Working Temperature F	32 to 650 degree
Working Temperature C	0 to 343 degrees
Propellant	DME/152A
NFPA Aerosol Flammability Level	1
DOT Proper Shipping Name	UN 1950, Aeros
VOC % (Federal)	60
VOC g/L (Federal)	441.96
VOC lbs./Gal (Federal)	3.68
Removal	Remove with or
Independent Certifications	UL recognized

Economical Paintable mold release requires no special cleaning. It will not interfere with part bonding, heat sealing, laminating, ultrasonic welding or post-decorating operations. You get perfect finishes every time and more cycles per can over other comparable releases.

ol Release S rless Liquid ne Fluid es s sols, Flammable, 2.1, Limited Quantity ganic or hydrocarbon solvents



Southwest Heater and Controls

800-687-2220

www.swhc.com

sales@swhc.com