SLIDE.

TECHNICAL DATA SHEET







Polycarbonate Mold Release Aerosol 41412

Product Description

It's all in the name. Polycarbonate mold release. Specially developed for polycarbonate resins, it will not interfere with part bonding, heat sealing, laminating, ultrasonic welding or post-decorating. Approved by SABIC for use with Lexan* resin. *Lexan is a registered trademark of SABIC.

Applications	Mold Release
Unit Package Description	16 ounce aerosol
Generic Description	Mold Release for Polycarbonate Resin
Net Weight Fill	11.5 net ounces
UPC Code	858799000141
Appearance	Clear Oily Colorless Liquid
Odor	Ether like
Flash Point F	Not Applicable
Flash Point C	Not Applicable
Base Type	Paintable Silicone Fluid
Evaporation Rate	Fast
HMIS Rating	1, 3, 0, B
DOT Proper Shipping Name	UN 1950, Aerosols, Flammable, 2.1, Limited Quantity
VOC % (Federal)	57.49
VOC g/L (Federal)	506.2
VOC lbs./Gal (Federal)	4.224
Removal	Remove with organic or hydrocarbon solvents
Units Per Case	12
Case Weight (Ibs)	13
Working Temperature F	32 to 650 degrees
Working Temperature C	0 to 343 degrees
Propellant	DME/152A
NFPA Aerosol Flammability Level	3
Independent Certifications	UL recognized



Southwest Heater and Controls

800-687-2220

www.swhc.com